



## **HYDROKINDO 4001-50**

### **I. DESCRIPTION**

HYDROKINDO 4001-50 is a selected mix latices which have excellent adhesion, good hardness, high durability, good chemical & good water resistance.

### **II. PROPERTIES**

- Excellent adhesion
- Good hardness
- Good chemical resistance
- Good water resistance

### **III. SUGGESTED USES**

- Economical Wall Paint
- Economical Wall Putty
- High Quality Exterior Wood Working Adhesive
- Economical Wood Coating

### **IV. SPECIFICATION**

- NV (% by wt, 150°C – 15 minutes) : 50 ± 1
- Viscosity (cps, Brookfield RVT 6, 20RPM, 30°C) : 15,000 – 35,000
- pH : 4.0 – 5.0
- Appearance : Milky white

### **V. TYPICAL PROPERTIES**

- Resin type : Self-crosslink emulsion
- Transition Glass Theoretical [°C] : 24

### **VI. PACKING**

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

### **VII. STORAGE**

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.