



HYDROKINDO 9810-35

I. DESCRIPTION

HYDROKINDO 9810-35 is an oil-modified urethane dispersion which curing undergoes oxidative drying to form excellent wear resistance film such as excellent hardness, resistance to hot & cold water, chemicals, alcohol & abrasion.

II. PROPERTIES

- Excellent hardness
- Excellent hot & cold water resistance
- Good scratch resistance
- Good chemical resistance
- Good gloss
- Good flow & leveling
- Fast dry
- Good wetting

III. SUGGESTED USES

- Single pack wooden parquet & furniture coating
- Interior & Exterior wood finishes

IV. SPECIFICATION

- NV (% by wt, 150°C – 15 minutes) : 35 ± 1
- Viscosity (cps, Brookfield LVT 2, 60RPM, 25°C) : max. 300
- pH : 7.0 - 9.0
- Appearance : Milky white dispersion - Dries clear

V. TYPICAL PROPERTIES

- Resin type : Oil-modified Urethane
- Solvent : NMP

VI. PACKING

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

VII. STORAGE

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.