



ALKINDO 5298-65

I. DESCRIPTION

ALKINDO 5298-65 is linear polyester which has excellent mechanical properties, good adhesion and good outdoor durability designed for coil coating.

II. PROPERTIES

- Excellent mechanical properties
- Good outdoor durability
- Good adhesion
- Good toughness

III. SUGGESTED USES

- Coil Coating

IV. COMPOSITION

- Acid type : mixed acid
- OHN (solid) : 30
- Solvent : pegasol 150, butyl cellosolve

V. SPECIFICATION

- NV (%) : 65 ± 1
- Viscosity (G-H, 25°C) : Z2 – Z4
- AV solution (mg KOH/g) : max. 5
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : slightly dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable.

VII. PACKING

Resin is supplied in steel drum with net. content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.