



ALKINDO 3124-60SS

I. DESCRIPTION

ALKINDO 3124-60SS is a short oil alkyd resin based on coconut oil with good gloss, good inter coat adhesion and non yellowing, suitable for can and general metal coating.

II. PROPERTIES

- Good gloss
- Good inter coat adhesion
- Good flow
- Whiteness
- Non yellowing

III. SUGGESTED USES

- Can coating
- General metal coating

IV. COMPOSITION

- Oil type : coconut oil
- Oil length : 36%
- PA content : 44%
- OHN (solid) : 170
- Solvent : pegasol 150

V. SPECIFICATION

- NV (%) : 60 ± 1
- Viscosity (G-H, 25°C) : Z₃ – Z₅
- AV solution (mg KOH/g) : max. 10
- Color (Gardner) : max. 2
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net. content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.