



ALKINDO 3939-60M

I. DESCRIPTION

ALKINDO 3939-60M is a fast solvent release short oil alkyd resin based on tall oil fatty acid with good leveling, hardness and sand ability, suitable for sealer and matt Polyurethane finishes for wood.

II. PROPERTIES

- Fast solvent release
- Good leveling
- Hardness
- Sand ability

III. SUGGESTED USES

- Sealer and matt Polyurethane finishes for wood

IV. COMPOSITION

- Fatty acid type : tall oil fatty acid
- Oil length : 33%
- PA content : 25%
- OHN (solid) : 110
- Solvent : xylene

V. SPECIFICATION

- NV (%) : 60 ± 1
- Viscosity (G-H, 25°C) : $Z_4 - Z_6$
- AV solution (mg KOH/g) : max. 15
- Color (Gardner) : max. 4
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.