

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ACRYLINDO 1106-42

I. DESCRIPTION

ACRYLINDO 1106-42 is a thermoplastic acrylic resin with good pigment dispersion and excellent stability for gold/silver ink, designed for paper coating.

II. PROPERTIES

- Flexible
- Good adhesion to paper

- Good pigment dispersion
- Excellent stability for gold/silver ink

III. SUGGESTED USES

Paper coating

IV. TYPICAL PROPERTIES

• Resin type : thermoplastic

• Solvent : toluene

• Tg (°C) : 59 (Shimadzu DSC-50)

V. SPECIFICATION

NV (%) : 42 ± 2
 Viscosity (G-H, 25°C) : Y - Z₁
 AV solution (mg KOH/g) : max. 1
 Color (Gardner) : max. 1

• Appearance : clean and clear

VI. DILUTABILITY

Aliphatic hydrocarbon : not dilutable
 Aromatic hydrocarbon : dilutable
 Ester : dilutable
 Ketone : dilutable
 Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251