



ACRYLINDO 1111-50X

I. DESCRIPTION

ACRYLINDO 1111-50X is a thermoplastic acrylic resin with good water resistance and dust proof, suitable for roof coating and masonry coating.

II. PROPERTIES

- Good UV retention
- Good water resistance
- Color retention
- Hardness
- Adhesion
- Dust proof

III. SUGGESTED USES

- Roof coating
- Masonry coating

IV. TYPICAL PROPERTIES

- Resin type : thermoplastic
- Solvent : xylene
butyl cellosolve
- Tg (°C) : 45 (Shimadzu DSC-50)

V. SPECIFICATION

- NV (%) : 50 ± 2
- Viscosity (G-H, 25°C) : $Z_5 - Z_6$
- AV solution (mg KOH/g) : 4 - 6
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.