



## ACRYLINDO 1114-50

### I. DESCRIPTION

ACRYLINDO 1114-50 is a thermoplastic acrylic resin with high gloss and good chemical resistance, designed for automotive refinish coating.

### II. PROPERTIES

- High gloss
- Fast drying
- Hardness
- Water and chemical resistance

### III. SUGGESTED USES

- Automotive refinish

### IV. TYPICAL PROPERTIES

- Resin type : thermoplastic
- Solvent : xylene  
n-butyl acetate
- Tg (°C) : 74

### V. SPECIFICATION

- NV (%) :  $50 \pm 1$
- Viscosity (G-H, 25°C) : Z<sub>1</sub> – Z<sub>3</sub>
- AV solution (mg KOH/g) : 4 - 6
- Color (Gardner) : max. 1
- Appearance : clean and clear

### VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

### VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.