TECHNICAL DATA

# **ACRYLINDO 1123-50**

# I. DESCRIPTION

ACRYLINDO 1123-50 is a thermoplastic acrylic resin with high gloss and fast tack free, suitable for automotive refinishes mainly as base coates.

### II. PROPERTIES

High gloss

• Hardness

• Water and chemical resistance

• Fast tack free

## III. SUGGESTED USES

Automotive refinishes.

#### IV. TYPICAL PROPERTIES

• Resin type : thermoplastic

• Solvent : xylene

n-butyl acetate

• Tg (C) : 86

#### V. SPECIFICATION

NV (%) : 50 ± 1
 Viscosity (G-H, 25°C) : Z<sub>1</sub> - Z<sub>3</sub>
 AV solution (mg KOH/g) : 4 - 6
 Color (Gardner) : max. 1

Appearance : clean and clear

#### VI. DILUTABILITY

Aliphatic hydrocarbon
Aromatic hydrocarbon
Ester
Ketone
Alcohol
not dilutable
dilutable
dilutable
dilutable
dilutable
dilutable

#### VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

## VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251

Email: alkindo@cbn.net.id