



ACRYLINDO 1126-50

I. DESCRIPTION

ACRYLINDO 1126-50 is a thermoplastic acrylic resin with outstanding gasoline and plasticizer resistance, good hardness, and good alcohol and oil resistance as well.

II. PROPERTIES

- Outstanding gasoline & plasticizer resistance
- Good hardness
- Compatible with CAB and Vinyl resin
- Good pigment orientation
- Good alcohol & oil resistance

III. SUGGESTED USES

- Plastic (ABS and HIPS) coating

IV. TYPICAL PROPERTIES

- Resin type : thermoplastic
- Solvent : toluene
isobutanol
- Tg (°C) : 64 (Shimadzu DSC-50)

V. SPECIFICATION

- NV (%) : 50 ± 1
- Viscosity (G-H, 25°C) : Z₄ – Z₆
- AV solution (mg KOH/g) : max. 3
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.