PT. ALKINDO MITRARAYA HIGH POLYMER

ACRYLINDO 1127-50

I. DESCRIPTION

ACRYLINDO 1127-50 is a thermoplastic acrylic resin which is dilutable in mineral spirit solvent. It was designed for architectural and repair paint due to low odor.

II. PROPERTIES

- Compatible with long oil alkyd
- Low odor

- Good leveling
- Balance between hardness and flexibility

III. SUGGESTED USES

Masonry coating

• Decorative coating

IV. TYPICAL PROPERTIES

 Resin type
Solvent
thermoplastic
pegasol 150 toluene dowanol PM
Tg (°C)
59

V. SPECIFICATION

- NV (%)
- Viscosity (G-H, 25°C) : Y Z₂
- AV solution (mg KOH/g) : max. 3
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

 $: 50 \pm 1$

VIII. STORAGE

Store in proper warehouse. Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.