

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ACRYLINDO 1202-60

I. DESCRIPTION

ACRYLINDO 1202-60 is a thermosetting acrylic resin with good adhesion, excellent flexibility, designed for clear-can coating.

II. PROPERTIES

Good adhesionGood chemical resistanceGloss

III. SUGGESTED USES

• Can coating-clear varnishes

IV. TYPICAL PROPERTIES

Resin type : thermosettingSolvent : n-butanol pegasol 100

V. SPECIFICATION

NV (%) : 60 ± 2
 Viscosity (G-H, 25°C) : X - Z₁
 AV solution (mg KOH/g) : 10 - 13
 Color (Gardner) : max. 1

Appearance : Clean and clear

VI. DILUTABILITY

Aliphatic hydrocarbon
Aromatic hydrocarbon
Ester
Ketone
Alcohol
not dilutable
dilutable
dilutable
dilutable
dilutable
dilutable
dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251