



ACRYLINDO 1206-50

I. DESCRIPTION

ACRYLINDO 1206-50 is a thermosetting acrylic resin with excellent storage stability, good gasoline resistance, and good flexibility; suitable for metal coating.

II. PROPERTIES

- Good gasoline resistance
- Good flexibility
- Hardness
- Excellent storage stability

III. SUGGESTED USES

- Metal coating

IV. TYPICAL PROPERTIES

- Resin type : thermosetting
- Solvent : Xylene
n-Butanol

V. SPECIFICATION

- NV (%) : 50 ± 1
- Viscosity (G-H, 25°C) : R – V
- AV solution (mg KOH/g) : 4 – 6
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.