

# PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

## **ACRYLINDO 1208-60**

### I. DESCRIPTION

ACRYLINDO 1208-60 is a thermosetting acrylic resin with good alkali and acid resistance, good adhesion, hardness, and gloss, designed for baking enamel.

### II. PROPERTIES

• Good adhesion • Hardness

Good alkali and acid resistance
 Gloss

#### III. SUGGESTED USES

• General metal coating – baking enamel

### IV. TYPICAL PROPERTIES

Resin type : thermosettingSolvent : n-butanol pegasol 100

### V. SPECIFICATION

NV (%) : 60 ± 2
 Viscosity (G-H, 25°C) : X - Z<sub>1</sub>
 AV solution (mg KOH/g) : 3 - 5
 Color (Gardner) : max. 1

Appearance : clean and clear

### VI. DILUTABILITY

Aliphatic hydrocarbon
Aromatic hydrocarbon
Ester
Ketone
Alcohol
not dilutable
dilutable
dilutable
dilutable
dilutable
dilutable

### VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

### VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251