



## **ACRYLINDO 1311-50**

### **I. DESCRIPTION**

ACRYLINDO 1311-50 is an acrylic polyol resin with good stain and chemical resistance, designed for wood and heavy-duty coating.

### **II. PROPERTIES**

- Good yellowing resistance
- Good chemical resistance
- Color retention
- Good stain resistance

### **III. SUGGESTED USES**

- Excellent PU coating for wood and heavy-duty

### **IV. TYPICAL PROPERTIES**

- Resin type : polyol
- Solvent : n-Butyl acetate  
Cellosolve acetate
- OHN (solid) : 199

### **V. SPECIFICATION**

- NV (%) :  $50 \pm 1.5$
- Viscosity (G-H, 25°C) : W – Y
- AV solution (mg KOH/g) : max. 5
- Color (Gardner) : max. 1
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : not dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.