



## **ACRYLINDO 1314-50**

### **I. DESCRIPTION**

ACRYLINDO 1314-50 is an acrylic polyol resin with fast curing, good color retention, and good wetting; suitable for PU both sanding sealer and high quality, and automotive refinish coating.

### **II. PROPERTIES**

- Good yellowing resistance
- Good chemical and stain resistance
- Good wetting
- Color retention
- Fast curing

### **III. SUGGESTED USES**

- PU sanding sealer
- Automotive refinish
- High quality polyurethane

### **IV. TYPICAL PROPERTIES**

- Resin type : polyol
- Solvent : n-Butyl acetate  
Xylene
- OHN (solid) : 99

### **V. SPECIFICATION**

- NV (%) :  $50 \pm 1$
- Viscosity (G-H, 25°C) : Z – Z<sub>2</sub>
- AV solution (mg KOH/g) : max. 5
- Color (Gardner) : max. 1
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.