



ACRYLINDO 1314-50 AF

I. DESCRIPTION

ACRYLINDO 1314-50 AF is a polyol acrylic resin with good yellowing resistance.

II. PROPERTIES

- Good yellowing resistance
- Good chemical resistance
- Good stain resistance
- Color retention
- Hardness
- Adhesion

III. SUGGESTED USES

- Wood coating

IV. TYPICAL PROPERTIES

- Resin type : polyol
- Solvent : n-Butyl acetate
Arcosolve PMA

V. SPECIFICATION

- NV (%) : 50 ± 1
- Viscosity (G-H, 25°C) : $Z - Z_2$
- AV (mg KOH/g) : max. 5,0
- Color (Gardner) : max. 1
- Appearance : clean and clear
- OHV : 99,25

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.