



## **ACRYLINDO 1317-60**

### **I. DESCRIPTION**

ACRYLINDO 1317-60 is an acrylic polyol resin with outstanding appearance, suitable for metal, automotive, and heavy-duty coating.

### **II. PROPERTIES**

- Outstanding appearance
- Good gloss retention
- Weather ability

### **III. SUGGESTED USES**

- Metal & automotive refinish coating
- Heavy duty coating

### **IV. TYPICAL PROPERTIES**

- Resin type : polyol
- Solvent : xylene
- OHN (solid) : 89

### **V. SPECIFICATION**

- NV (%) :  $60 \pm 2$
- Viscosity (G-H, 25°C) :  $Z_3 - Z_5$
- AV solution (mg KOH/g) : max. 3
- Color (Gardner) : max. 1
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.