



## **ACRYLINDO 1318-43**

### **I. DESCRIPTION**

ACRYLINDO 1318-43 is an acrylic polyol resin with good yellowing and stain resistance, and fast curing, designed for matt top coat-wood finishes.

### **II. PROPERTIES**

- Good yellowing resistance
- Good chemical and stain resistance
- Fast curing
- Color retention
- Hardness

### **III. SUGGESTED USES**

- Matt top coat-wood finishes

### **IV. TYPICAL PROPERTIES**

- Resin type : polyol
- Solvent : xylene  
n-butyl acetate  
arcosolve PMA
- OHN (solid) : 103

### **V. SPECIFICATION**

- NV (%) :  $43 \pm 1$
- Viscosity (G-H, 25°C) :  $Z_1 - Z_3$
- AV solution (mg KOH/g) : max. 7
- Color (Gardner) : max. 1
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.