



ACRYLINDO 1323-55

I. DESCRIPTION

ACRYLINDO 1323-55 is an acrylic polyol resin with good gloss, balanced in hardness and flexibility, suitable for automotive refinish coating and plastic coating.

II. PROPERTIES

- Good gloss
- Good adhesion
- Balance in hardness & flexibility
- Fast reactive

III. SUGGESTED USES

- Automotive refinish coating
- Plastic coating

IV. TYPICAL PROPERTIES

- Resin type : polyol
- Solvent : Xylene
n-Butyl acetate
- OHN (solid) : 74

V. SPECIFICATION

- NV (%) : 55 ± 1
- Viscosity (G-H, 25°C) : X – Z₁
- AV solution (mg KOH/g) : max. 10
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : not dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.