

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ACRYLINDO 1325-70

I. DESCRIPTION

ACRYLINDO 1325-70 is an acrylic polyol resin with excellent gloss, good wetting and adhesion, good film built and levelling, suitable for plastic coating.

II. PROPERTIES

Good adhesion

Good film built

Good leveling

Flexible

III. SUGGESTED USES

Plastic coating

Automotive clear coat

IV. TYPICAL PROPERTIES

• Resin type : polyol

• Solvent : butyl acetate

• OHN (solid) : 107

V. SPECIFICATION

NV (%) : 70 ± 1
 Viscosity (G-H, 25°C) : Z₁ - Z₃
 AV solution (mg KOH/g) : max. 5
 Color (Gardner) : max. 1

Appearance : clean and clear

VI. DILUTABILITY

Aliphatic hydrocarbon : not dilutable
Aromatic hydrocarbon : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251