

# PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

## **ALKINDO 1821-60**

#### I. DESCRIPTION

ALKINDO 1821-60 is a long oil alkyd resin based on mixed oil with outstanding in drying time, hardness, color & gloss retention, and durability, suitable for architectural paints, do it yourself paint, interior and exterior decorative.

#### II. PROPERTIES

Outstanding fast dry

• Color & gloss retention

• Hardness

• Gloss

• Durability

#### III. SUGGESTED USES

Architectural paints

• Do it yourself paint

• Interior & exterior decorative

#### IV. COMPOSITION

Oil type : mixed oil
Oil length : 63%
PA content : 25%

• Solvent : white spirit

### V. SPECIFICATION

NV (%) : 60 ± 1
 Viscosity (G-H, 25°C) : Z - Z<sub>2</sub>
 AV solution (mg KOH/g) : max. 10
 Color (Gardner) : max. 5

Appearance : Slightly hazy

#### VI. DILUTABILITY

Aliphatic : dilutable
Aromatic : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : not dilutable

#### VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

#### VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251