

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ALKINDO 2822-60

I. DESCRIPTION

ALKINDO 2822-60 is a medium oil alkyd resin based on soybean oil with good hardness, fast dry, good flexibility, whiteness & yellowing resistance, suitable for fast dry decorative enamel.

II. PROPERTIES

Fast dry

• Good whiteness and yellowing resistance

Good hardness and flexibility

III. SUGGESTED USES

• Fast dry decorative enamel

IV. COMPOSITION

• Oil type : soybean oil

Oil length : 50%PA content : 27%

Solvent : white spirit

V. SPECIFICATION

• NV (%) : 60 ±1

• Viscosity (G-H, 25°C) : Z_2+-Z_4+ (50% in white spirit)

AV solution (mg KOH/g) : max. 7.5Color (Gardner) : max. 3

Appearance : clean and clear

VI. DILUTABILITY

Aliphatic : dilutable
Aromatic : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251