

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ALKINDO 3133-70

I. DESCRIPTION

ALKINDO 3133-70 is a short oil alkyd resin based on coconut oil with excellent whiteness, color retention, gloss, wetting, flexible, and good compatibility with NC suitable for economical wood finishes.

II.PROPERTIES

Excellent whiteness
 Color retention

• Gloss • Wetting

• Flexible

III. SUGGESTED USES

Acid curing wood finishes
 NC system

Polyurethane coating

IV. COMPOSITION

• Oil type : coconut oil

Oil length : 32%
 PA content : 47%
 OHN (solid) : 140
 Solvent : xylene

V. SPECIFICATION

• NV (%) : 70 + 1

• Viscosity (G-H, 25°C) : Z₅ – Z₆ (60% in xylene)

AV solution (mg KOH/g) : max. 10Color (Gardner) : max. 2

• Appearance : clean and clear

VI. DILUTABILITY

Aliphatic : not dilutable
Aromatic : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251