



ALKINDO 3404-70

I. DESCRIPTION

ALKINDO 3404-70 is an aromatic free short oil alkyd resin based on mixed fatty acid with good gloss, alkali resistance, and good wetting, suitable for solid color polyurethane and concrete panel polyurethane.

II. PROPERTIES

- Good gloss
- Alkali resistance
- Good wetting

III. SUGGESTED USES

- Solid color PU
- Concrete panel PU

IV. COMPOSITION

- Fatty acid type : mixed fatty acid
- Oil length : 40%
- PA content : 31%
- OHN (solid) : 165
- Solvent : n-butyl acetate (aromatic free)

V. SPECIFICATION

- NV (%) : 70 ± 1
- Viscosity (G-H, 25°C) : X – Z₁
- AV solution (mg KOH/g) : max. 7
- Color (Gardner) : max. 4
- Appearance : slightly hazy

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.