

PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

ALKINDO 3803-70 AF

I. DESCRIPTION

ALKINDO 3803-70 AF is an aromatic free type of ALK 3803-60, based on soybean fatty acid with good pigment dispersion and good compatibility with wide range of resins, suitable for industrial universal pigment paste.

II. PROPERTIES

- Good wetting
- Good chemical resistance
- Compatible with various kinds of resin mainly short oil and medium oil alkyd

III. SUGGESTED USES

Industrial universal pigment paste

IV. COMPOSITION

Fatty acid type : soybean fatty acid

Oil length : 44%
 PA content : 36%
 OHN : 154

Solvent : Arcosolve PMA

V. SPECIFICATION

NV (%) : 70 ± 1
 Viscosity (G-H, 25°C) : W - Z
 AV (mg KOH/g) : max. 8
 Color (Gardner) : max. 5

Appearance : clean and clear

VI. DILUTABILITY

Aliphatic : not dilutable
Aromatic : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251