



ALKINDO 3827-50

I. DESCRIPTION

ALKINDO 3827-50 is a short oil alkyd resin based on mixed oil with good build, balance in hardness and flexibility, gloss, suitable for industrial coating.

II. PROPERTIES

- Toughness
- Good film build
- Gloss

III. SUGGESTED USES

- Wood finishes

IV. COMPOSITION

- Oil type : mixed oil
- Oil length : 32%
- PA content : 45%
- OHN (solid) : 160
- Solvent : Xylene
MEK

V. SPECIFICATION

- NV (%) : 50 ± 1
- Viscosity (G-H, 25°C) : X – Z₁
- AV solution (mg KOH/g) : max. 15
- Color (Gardner) : max. 2
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.