

# PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

# **ALKINDO 3903-60B**

#### I. DESCRIPTION

ALKINDO 3903-60B is a short oil alkyd resin based on castor oil with excellent chemical resistance and built, good gloss and color retention. It is medium flexible for clear lacquer and polyurethane top coat.

#### II. PROPERTIES

- Tough
- Good gloss

- Excellent chemical resistance and built
- Good color retention

## III. SUGGESTED USES

- Clear lacquer
- Polyurethane

#### IV. COMPOSITION

Oil type : castor oil
 Oil length : 34%
 PA content : 36%
 OHN (solid) : 145
 Solvent : toluene

#### V. SPECIFICATION

NV (%) : 60 ± 1
 Viscosity (G-H, 25°C) : Q - T
 AV solution (mg KOH/g) : max. 10
 Color (Gardner) : max. 4

Appearance : clean and clear

#### VI. DILUTABILITY

Aliphatic : not dilutable
Aromatic : dilutable
Ester : dilutable
Ketone : dilutable
Alcohol : dilutable

#### VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

## VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251