



## **ALKINDO 3904-65B AF**

### **I. DESCRIPTION**

ALKINDO 3904-65B AF is an aromatic free of short oil alkyd resin based on castor oil with excellent film built and body with good chemical resistance. It is high quality resin for polyurethane sanding sealer.

### **II. PROPERTIES**

- Fast dry
- Hardness
- Good gloss
- Excellent built & body
- Good color retention

### **III. SUGGESTED USES**

- High quality polyurethane sanding sealer

### **IV. COMPOSITION**

- Oil type : castor oil
- Oil length : 31%
- PA content : 40%
- OHN : 150
- Solvent : n-butyl acetate (aromatic free)

### **V. SPECIFICATION**

- NV (%) : 65 ± 1
- Viscosity (G-H, 25°C) : Z<sub>2</sub> – Z<sub>4</sub>
- AV (mg KOH/g) : 12 – 20
- Color (Gardner) : max. 6
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.