



## **ALKINDO 4259-50**

### **I. DESCRIPTION**

ALKINDO 4259-50 is a urethane alkyd resin based on linseed oil with outstanding in drying time, good recoat ability, chemical & abrasive resistance, especially for interior finishes.

### **II. PROPERTIES**

- Outstanding in drying time
- Good recoat ability
- Chemical & abrasive resistance

### **III. SUGGESTED USES**

- Industrial wood stain
- Parquet flooring

### **IV. COMPOSITION**

- Oil type : linseed oil
- Modifier : toluene diisocyanate
- Free isocyanate content : max. 0.5%
- Solvent : white spirit

### **V. SPECIFICATION**

- NV (%) :  $50 \pm 2$
- Viscosity (G-H, 25°C) : X – Z<sub>1</sub>
- AV solution (mg KOH/g) : max. 2
- Color (Gardner) : max. 5
- Appearance : clean and clear

### **VI. DILUTABILITY**

- Aliphatic : dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

### **VII. PACKING**

Resin is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse.

Keep container closed when not in use.

---

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

---