



ALKINDO 4802-55

I. DESCRIPTION

ALKINDO 4802-55 is a polyurethane alkyd resin, with good adhesion and wetting properties, designed for interior quick dry coating.

II. PROPERTIES

- Fast dry
- Good adhesion
- Good wetting and levelling

III. SUGGESTED USES

- Floor varnishes
- Transparent wood stain
- Decorative paint

IV. COMPOSITION

- Oil type : mixed oil
- Modifier : toluene diisocyanate
- Free isocyanate content : max. 0.1 %
- Solvent : pegasol 150

V. SPECIFICATION

- NV (%) : 55 ± 1
- Viscosity (G-H, 25°C) : X – Z₁
- AV solution (mg KOH/g) : max. 3
- Color (Gardner) : max. 6
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.