



ALKINDO 5202 – 60LV

I. DESCRIPTION

ALKINDO 5202-60LV is low branched polyester for use in combination with amino- and/or pre-polymerized isocyanate resins for can and coil coating formulations and PU sealer wood finishes. ALKINDO 5202-60LV provides very good flow and is suitable for roller applications, good adhesion for printing inks, has gloss retention, excellent flexibility and overcome hair crack of soft wood.

II. PROPERTIES

- Very good flow
- Good adhesion
- Good wetting
- Gloss retention
- Excellent Flexibility

III. SUGGESTED USES

- Can & coil coating
- PU sealer wood finishes

IV. COMPOSITION

- Acid type : PA
- PA (%) : 43
- OHN (solid) : 54
- Solvent : Pegasol 150

V. SPECIFICATION

- NV (%) : 60 ± 1
- Viscosity (G-H, 25°C) : X – Z
- AV solution (mg KOH/g) : max. 10
- Color (Gardner) : max. 3
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net. content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.