



ALKINDO 5213-75

I. DESCRIPTION

ALKINDO 5213-75 is a slightly branched, fatty acid-modified saturated polyester resin, which offers outstanding flexibility, good hardness, supplied in low viscosity and is design for fast drying polyurethane coating based on polyisocyanate with long pot-life.

II. PROPERTIES

- Fast drying
- Excellent flexibility
- Low molecular weight
- Long Pot-Life
- Good Hardness
- Non Yellowing

III. SUGGESTED USES

- Fast Drying Coating in PU system

IV. COMPOSITION

- Acid type : Phthalic Anhydride
- OHN (solid) : 187
- Solvent : Butyl Acetate, Xylene

V. SPECIFICATION

- NV (%) : 75 ± 1
- Viscosity (G-H, 25°C) : Y – Z₂
- AV solution (mg KOH/g) : max. 12
- Color (Gardner) : max. 3
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net. content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.