



ALKINDO 5703-80

I. DESCRIPTION

ALKINDO 5703-80 is a low viscosity and reactive modified polyester resin with high-wetting property toward pigments & fillers and excellent compatibility with wide range of paints binders, suitable for universal pigment paste.

II. PROPERTIES

- Excellent compatibility with wide range of resin
- Good color retention
- Excellent wetting

III. APPLICATION

- Universal pigment paste for Do It Yourself, NC, PU & stoving enamel

IV. COMPOSITION

- Acid type : PA
- PA (%) : 35
- OHN (solid) : 100
- Solvent : Xylene

V. SPECIFICATION

- NV (%) : 80 ± 1
- Viscosity (G-H, 25°C) : $Z_2 - Z_4$
- AV solution (mg KOH/g) : max. 8
- Color (Gardner) : max. 8
- Appearance : very slightly hazy

VI. DILUTABILITY

- Aliphatic : dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.