



AMINDO 6759-72

I. DESCRIPTION

AMINDO 6759-72 is a high quality resin having good mechanical properties, suitable for interior coatings for high quality demand.

II. PROPERTIES

- Good mechanical properties
- Resistance to heat, detergent, dilute acids and alkalis

III. SUGGESTED USES

- Interior coatings for high quality demand

IV. TYPICAL PROPERTIES

- Resin type : Benzoguanamine formaldehyde resin
- Alkylation : n-butylated
- Solvent : n-butanol
Xylene

V. SPECIFICATION

- NV (% , 120°C – 2 hours) : 72 ± 2
- Viscosity (G-H, 25°C) : T – W
- Viscosity (cps, 25°C) : 650 – 1000
- AV solution (mg KOH/g) : max. 1
- Exxsol D-30 Tol (mL/g) : min. 4
- Appearance : clean and clear
- FF content (%) : max. 1.1
- Color (Gardner) : max. 1

VI. DILUTABILITY

- Aliphatic hydrocarbon : partially dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.
