



AMINDO 7703-60X

I. DESCRIPTION

AMINDO 7703-60X is a butylated urea formaldehyde resin with excellent compatibility with epoxy and good adhesion & stability, suitable for epoxy primer and general purpose enamel.

II. PROPERTIES

- Excellent compatibility with epoxy
- Good adhesion & stability

III. SUGGESTED USES

- Epoxy primer
- General purpose enamel

IV. TYPICAL PROPERTIES

- Resin type : Urea formaldehyde resin
- Alkylation : n-Butylated
- Solvent : n-butanol
Xylene

V. SPECIFICATION

- NV (% , 150°C – 15 min) : 60 ± 2
- Viscosity (G-H, 25°C) : T – W
- Viscosity (cps, 25°C) : 550 – 1070
- AV solution (mg KOH/g) : max. 3
- ASTM Tolerance (mL/g) : min. 2.0
- Color (Gardner) : max. 1
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : partially dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.