



AMINDO 7740-60

I. DESCRIPTION

AMINDO 7740-60 is a highly butylated resin having a good flow and flexibility, designed for flow control additive in epoxy system.

II. PROPERTIES

- Good flow and flexibility
- Flow promoter and levelling agent for epoxy system

III. SUGGESTED USES

- Flow control additive in epoxy systems

IV. TYPICAL PROPERTIES

- Resin type : Urea formaldehyde resin
- Alkylation : n-butylated
- Solvent : n-butanol
Xylene

V. SPECIFICATION

- NV (% , 150°C – 15 min) : 60 ± 2
- Viscosity (G-H, 25°C) : T – W
- Viscosity (cps, 25°C) : 550 – 1070
- AV solution (mg KOH/g) : max. 3.0
- ASTM Tolerance (mL/g) : min. 1.8
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic hydrocarbon : partially dilutable
- Aromatic hydrocarbon : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.