

# PT. ALKINDO MITRARAYA HIGH POLYMER

TECHNICAL DATA

## CROSSLINDO 0430

#### I. DESCRIPTION

CROSSLINDO 0430 is a reactive aliphatic, less hygroscopic polyamine which has good hardness and good clarity. It is designed as cross-linking agent for liquid epoxy resins. It has good workability and rapid cure at room temperature still delivering convenient viscosity at mixing rates. It is particularly suitable for colorless coatings or adhesive systems.

### II. PROPERTIES

Good hardness
 Good clarity and leveling

Good wetting properties
 Low viscosity

#### III. SUGGESTED USES

• Epoxy hardener for civil projects (e.g. flooring)

• Maintenance paints

Two-pack adhesives

• Castings and hand lay-up laminates

#### IV. COMPOSITION

Modifier : Proprietary polyamine
 Amine Hydrogen Equivalent Weight : approx. 120 g/equivalent

#### V. SPECIFICATION

Viscosity (mPaS, 30°C) : max 120Color (Gardner) : max. 2

• Appearance : clear to light yellow liquid

• Density  $(25^{\circ}C)$  :  $1.00 - 1.10 \text{ g/cm}^3$ 

#### VI. COMPATIBILITY

Aromatic : dilutableEster : dilutableAlcohol : dilutable

#### VII. PACKING

The hardener is supplied in steel drum with net content 200 kgs.

#### VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Jl. Gatot Subroto Km. 8, Desa Kadu Jaya, Kecamatan Curug, Kabupaten Tangerang, INDONESIA - 15810

Phone: +62-21-59302250, Fax: +62-21-59302251