



---

## **CROSSLINDO 1375**

### **I. DESCRIPTION**

CROSSLINDO 1375 is a fast curing aromatic polyisocyanate based on toluene diisocyanate which has good gloss, good adhesion and good hardness. It is design for general metal coating, wooden furniture & floor coating.

### **II. PROPERTIES**

- Good hardness
- Good adhesion
- Fast curing
- Good gloss

### **III. SUGGESTED USES**

- Furniture coating
- Floor coating
- General PU metal coating

### **IV. COMPOSITION**

- Isocyanate based : Toluene diisocyanate
- Solvent : Ethyl acetate

### **V. SPECIFICATION**

- NV (% , 150°C for 15 min) : 75 ± 2
- Viscosity (G-H, 25°C) : Z<sub>4</sub> – Z<sub>6</sub>
- Color (Gardner) : max. 2
- Appearance : Transparent
- NCO Content (%) : 13 ± 1

### **VI. COMPATIBILITY**

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ketone : dilutable
- Ester : dilutable
- Alcohol : cannot be used (react spontaneously)

### **VII. PACKING**

The hardener is supplied in steel drum with net content 200 kgs.

### **VIII. STORAGE**

Store in proper warehouse & recommended storage temperature is 10 to 30°C  
Keep container closed when not in use.

---

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.