



---

## **HYDROKINDO 2003-50**

### **I. DESCRIPTION**

HYDROKINDO 2003-50 is a selected latex emulsion with excellent adhesion, excellent flexibility, high gloss & good durability, which is suitable for natural fiber coating.

### **II. PROPERTIES**

- Excellent adhesion
- Excellent flexibility
- High Gloss
- Good durability

### **III. SUGGESTED USES**

- Economical natural fiber coating

### **IV. SPECIFICATION**

- NV (% by wt, 150°C – 15 minutes) : 50 ± 1
- Viscosity (cps, Brookfield RVT 6, 20RPM, 30°C) : 20000 – 35000
- pH : 4.0 – 5.0
- Appearance : Milky white

### **V. TYPICAL PROPERTIES**

- Resin type : Selected Latex Emulsion
- Transition Glass Theoretical [°C] : ± 100

### **VI. PACKING**

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

### **VII. STORAGE**

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.

---

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.