



HYDROKINDO 4068-48

I. DESCRIPTION

HYDROKINDO 4068-48 is an emulsion of vinyl – veova – acrylic ester copolymer which has excellent adhesion, good dirt pick up resistance, high durability, good alkali & good water resistance.

II. PROPERTIES

- Excellent adhesion
- High durability
- Good dirt pick up resistance
- Good alkali resistance
- Good water resistance

III. SUGGESTED USES

- High quality interior & exterior Wall Paint

IV. SPECIFICATION

- | | |
|--|---------------|
| • NV (% by wt, 150°C – 15 minutes) | : 49 ± 1 |
| • Viscosity (cps, Brookfield LVT 3, 60RPM, 30°C) | : 100 – 600 |
| • pH | : 4.0 – 5.5 |
| • Appearance | : Milky white |

V. TYPICAL PROPERTIES

- | | |
|-------------------------------------|-------------------------------------|
| • Resin type | : Vinyl – Veova – Acrylic Copolymer |
| • Transition Glass Theoretical [°C] | : 20 |

VI. PACKING

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

VII. STORAGE

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.