



HYDROKINDO 5057-48

I. DESCRIPTION

HYDROKINDO 5057-48 is full acrylic latex emulsion which has excellent exterior durability, high block resistance, with fast hardness development.

II. PROPERTIES

- Excellent exterior durability
- High block resistance
- Fast hardness development

III. SUGGESTED USES

- Cementitious substrates
- High quality wood stain

IV. SPECIFICATION

- | | |
|--|---------------|
| • NV (% by wt, 150°C – 15 minutes) | : 48 ± 1 |
| • Viscosity (cps, Brookfield LVT 2, 60rpm, 30°C) | : 10 – 200 |
| • pH | : 9.0 – 10.0 |
| • Appearance | : Milky white |

V. TYPICAL PROPERTIES

- | | |
|-------------------------------------|----------------------|
| • Resin type | : Full Acrylic Latex |
| • Transition Glass Theoretical [°C] | : ± 42 |

VI. PACKING

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

VII. STORAGE

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.