



HYDROKINDO 5062-50

I. DESCRIPTION

HYDROKINDO 5062-50 is an acrylic polymer emulsion which has good abrasion resistance, good gloss, good adhesion, good alkali resistance, and high durability.

II. PROPERTIES

- Good abrasion resistance
- Good gloss and adhesion
- High durability
- Good alkali resistance

III. SUGGESTED USES

- Interior & Exterior high quality wall paint
- High gloss & semi gloss wood finishes
- Floor coatings

IV. SPECIFICATION

- NV (% by wt, 150°C – 15 minutes) : 50 ± 1
- Viscosity (cps, Brookfield LVT 2, 60rpm, 30°C) : max. 300
- pH : 9.0 – 10.0
- Appearance : Milky white

V. TYPICAL PROPERTIES

- Resin type : Acrylic Polymer Emulsion
- Tg [°C] : ± 18°C

VI. PACKING

Resin is packed 200 kgs netto in open head metal drums packed inside with 2 liners of HDPE plastic bags.

VII. STORAGE

Stored inside warehouse to avoid direct sunlight. Keep container closed when not in use. Storage life is 6 months after delivery.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.