



PLASTINDO 1008-90

I. DESCRIPTION

PLASTINDO 1008-90 is a high solid flexible alkyd based on linoleic rich with excellent durability and good penetration into the wood, gloss retention and outstanding in drying time.

II. PROPERTIES

- Excellent flexibility
- Excellent durability
- Fast dry
- Good gloss retention
- Good brush ability

III. SUGGESTED USES

- Exterior wood varnishes or pigmented paint
- Water breathable wood stain

IV. COMPOSITION

- Oil type : linoleic rich
- Oil length : 60 %
- Solvent : white spirit
xylene

V. SPECIFICATION

- NV (%) : 90 ± 1.5
- Viscosity (G-H, 25°C) : X – Z₁
- AV solution (mg KOH/g) : max. 10
- Color (Gardner) : max. 5
- Appearance : Clear & Clean

VI. DILUTABILITY

- Aliphatic : dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : dilutable

VII. PACKING

Resin is supplied in steel drum with net content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.