



ALKINDO 5211 – 80

I. DESCRIPTION

ALKINDO 5211-80 is high solid low-branched polyester for use in combination with pre-polymerized isocyanate resins for PU sealer wood finishes. ALKINDO 5211-80 provides very good flow and is suitable for roller applications, good adhesion, gloss retention, excellent flexibility and overcome hair crack of soft wood.

II. PROPERTIES

- Very good flow
- Good adhesion
- Good wetting
- Gloss retention
- Excellent Flexibility
- High solid

III. SUGGESTED USES

- PU sealer wood finishes

IV. COMPOSITION

- Acid type : mixed acid
- OHN (solid) : 62
- Solvent : n-Butyl Acetate

V. SPECIFICATION

- NV (%) : 80 ± 1
- Viscosity (G-H, 25°C) : $Z_3 - Z_5$
- AV solution (mg KOH/g) : max. 13
- Color (Gardner) : max. 2
- Appearance : clean and clear

VI. DILUTABILITY

- Aliphatic : not dilutable
- Aromatic : dilutable
- Ester : dilutable
- Ketone : dilutable
- Alcohol : not dilutable

VII. PACKING

Resin is supplied in steel drum with net. content 200 kgs.

VIII. STORAGE

Store in proper warehouse.

Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.